Raised Ranch

590/591 doorLin



Almond

WHITE - SHERWOOD WINDOW

590/591 psylighted

Raised Ranch Panel

Constructed of top quality materials, highly detailed louvered panel, deep woodgrain texture, and two coat prefinished paint system all combine to enhance the beauty of your home.

- 25 gauge steel
- 1.0 mil paint with 3 color options
- 6 window options
- R-value 6.85 *591 Feature
- Vinyl interior skin *591 Feature

Sandstone

White



Features



25 GAUGE STEEL

Hot dipped galvanized steel construction with hemmed inside return rail provides superior strength and durability.



ROLLED SAFETY EDGES ON SECTION JOINTS

Eliminates sharp edges, and provides extra strength.



19 GAUGE HOT DIPPED GALVANIZED STILES

Heavy duty metal stiles give strong rigid support for all hinges, rollers, and operator attachment.



STILES ATTACHED WITH RIVETS

Provides superior strength when compared to common sheet metal joining methods.



TONGUE AND GROOVE MEETING RAILS

For superior strength and better sealing against wind, rain, and snow.



RIGID ALUMINUM RETAINER WITH WEATHERSTRIP

Provides added strength while securing replaceable U-type bottom astragal weatherstrip to help keep the elements out.



R-VALUE 6.85

Enhances your home's energy savings, makes your door operation quieter, and reduces exterior noise in your garage. *591 Feature



HIGH IMPACT PLASTIC BACK COVER

Protects the insulation, and enhances the interior look of your garage door. *591 Feature



CFC FREE EXPANDED POLYSTYRENE

Environmentally friendly insulation that will not degrade with vibration or time. *591 Feature

Size Options

WIDTHS:





HEIGHTS: 6'6", 6'9", 7'0", 7'6", 7'9", 8'0"

*Contact your distributor for additional heights.

Window Options



#306 Sherwood



#305 Williamsburg



#591 Cascade



#397 Stockton



#597 Stockbridge



#897 Prairie

Window Glass Options

See website for glass options

*Not all glazing options may be available from all distributors. No glazing on 18" sections

Paint System



1.0 MIL PAINT SYSTEM

Includes .25 mil rust inhibiting primer and .75 mil exterior top coat that resists fading and chalking, while providing consistent color from panel to panel and more durability.

- 1 Paint .75 MIL
- 2 Primer .25 MIL
- 3 Stee
- 4 Primer .2 MIL
- 5 Paint .3 MIL

Construction



- 1 Tongue and groove meeting rails
- 2 Hemmed interior rails
- 3 2" thick section
- 4 19 gauge hot dipped galvanized steel stiles
- 5 CFC free expanded polystyrene insulation with vinyl backing (standard on 591)
- 6 Replaceable U-Type vinyl bottom weatherstrip
- 7 Extruded aluminum weatherstrip retainer











^{*}This image is showing 591